

PRECEPT HD PORCELAIN TILE

PACKAGING INFORMATION

DESCRIPTION	ITEM CODE				LBS/BOX	PCS/BOX	SQFT/BOX	BOXES/SKID	SQFT/SKID
	IVORY	CLAY	ICE	MICA					
12" x 24" PRECEPT HD PORCELAIN TILE	69-290	69-291	69-292	69-293	63.34	8	15.50	32	496
13" x 13" PRECEPT HD PORCELAIN TILE	63-513	63-514	63-515	63-516	54.43	13	15.28	46	702.88
10" x 20" PRECEPT HD GLOSSY WALL TILE	56-508	56-509	56-510	56-511	51.49	12	16.14	36	581.04
2" x 2" PRECEPT HD BASKETWEAVE PORC. MOSAICS	63-517	63-518	63-519	63-520	38.20	10	11.74	48	563.52
3" x 12" PRECEPT HD PORCELAIN BULLNOSE	69-294	69-295	69-296	69-297	16.46	20	n/a	n/a	n/a
3" x 10" PRECEPT HD GLOSSY BULLNOSE	56-512	56-513	56-514	56-515	15.00	25	n/a	n/a	n/a

GENERAL SPECIFICATIONS

DESCRIPTION	METHOD	UNIT	13" x 13"	12" x 24"
THICKNESS		mm – in	7.8 mm – 5/16"	9 mm – 11/32"
WATER ABSORPTION	EN ISO 10545-3	(%)	≤ 0.5	≤ 0.5
ABRASION RESISTANCE	EN ISO 10545-7	(PEI)	4	4
SCRATCH HARDNESS		(Mohs)	7	7
BREAKING STRENGTH	EN ISO 10545-4	(lbf)	≥ 330	≥ 450
CHEMICAL RESISTANCE	EN ISO 10545-13	(GL)	Class A – Resistant	Class A – Resistant
FROST RESISTANCE	EN ISO 10545-12		Resistant	Resistant
STATIC COEFFICIENT OF FRICTION (WET)	ASTM C-1028	(μ)	≥ 0.70	≥ 0.70
STATIC COEFFICIENT OF FRICTION (DRY)	ASTM C-1028	(μ)	≥ 0.80	≥ 0.80
DCOF (WET)	ANSI B101.3		≥ 0.60	≥ 0.60
SHADE VARIATION			V2	V2